



STANDARD LOW PRESSURE CYLINDERS

PART #	DESIGN						
	MIN. BURST psi	DIAMETER in	LENGTH in	MIN. WALL in	VOLUME cu in	NECK CONFIGURATION	ALUMINUM ALLOY
2325	600	2.520	6.560	0.028	25.5	0.96	1100
2327	600	2.520	6.500	0.028	25.5	1"-14UNS-2B	1100
2258	600	2.906	7.437	0.032	38.0	0.96	1100
2260	600	2.906	7.375	0.032	38.0	1"-14UNS-2B	1100
2392	600	2.906	10.537	0.032	56.0	0.96	1100
2394	600	2.906	10.475	0.032	56.0	1"-14UNS-2B	1100
1686	600	3.125	12.800	0.034	85.0	0.96	1100
2636	600	3.125	12.800	0.034	85.0	1"-14UNS-2B	1100
2611	1250	3.500	13.625	0.061	105.0	0.96	3003
2545	1440	4.000	13.750	0.072	136.0	1"-14UNS-2B	3003
1602	1440	4.000	17.125	0.072	174.0	1"-14UNS-2B	3003

Specification: - DOT 39, 2P or 2Q upon request
 - 2611 and 2545 are available with DOT 39 and TC-39M test qualifications

Cleaning: - Provided commercially clean
 - Special cleaning available upon request

Finish: - Cylinders are provided with natural aluminum exterior
 - Powder coating available upon request

Custom Sizes: - Many custom sizes and thread details are available

Catalina Cylinders East
 2400 Aluminum Avenue, Hampton, VA 23661
 tel 757-896-9100 fax 757-896-0206
sales@catalinacylinders.com
www.catalinacylinders.com